

WTR-HE2500 Portable Bearing Heater

WTR portable bearing heaters adopts metal thermal expansion and contraction characteristics, which can extend the service life of rolling bearings. Providing you with a convenient, economical, safe and reliable method of bearing installation.



- ◆ New eddy current sensing design
- ◆ Heatable sealed bearing (ZZ, 2RS)
- ◆ Continuous operation, high output power and high efficiency
- ◆ No open fire, no pollution, environmental protection and energy saving, no accidents
- ◆ Dual control of time and temperature, temperature control error $<3^{\circ}\text{C}$
- ◆ Automatic degaussing / manual degaussing, demagnetization standard $<2\text{A}/\text{CM}$
- ◆ Switch between heating time and real-time temperature in heating mode

Model	WTR-HE2500
Power	2.5KVA
V/HZ	220V/50HZ, 2Phase
Current	10A
Power connection	Plug
Power line length	1.5mm ² ;3m length
Column height	100mm
Column spacing	70mm
Workpiece Size Range	
Max. weight of the workpiece	12KG / 9KG
Bore size of the workpiece	15mm
Max. out size of the workpiece	220mm
Max. width of the workpiece	70mm / 100mm
Temperature Control	
Temperature range	0-240°C
Temperature sensor	K type
Digital display	Yes
Time control	
Time range	0-99'59''
Digital display	Yes
Heater size	240*200*235mm,15kg
Wooden case package size	460x370x410mm, 19kg
Yokes (5pcs)	10x10x150mm ; 14x14x150mm 20x20x150mm ; 30x30x150mm ; 40x40x150mm